



Art of inspiration

DECORATIVE FINISHING WAX

Francesco GUARDI Collezione

PRODUCT DESCRIPTION

The decorative finish wax for stuccos by Francesco GUARDI is an ideal product for highlighting colour and adding sheen to a limestone stucco surface. Apart from its decorative properties, the product is suitable for protecting the surface of limestone stuccos against water, moisture and mechanical abrasion, while making it easier to maintain the applied compound.

- Gives a natural shine
- Saturates the colour of the stucco
- Protects against moisture
- Highlights the depth of colour



INTENDED USE

The wax is designed to protect limestone stucco surfaces against water, moisture and mechanical abrasion. It adds shine, highlights the colour and facilitates the maintenance of the applied compound. The Francesco GUARDI wax is also perfectly suitable for shining and preserving all wooden surfaces (furniture, window/door frames, parquets, etc.), as well as surfaces made of marble, granite, stone, terracotta and any other waxable surfaces.

SUBSTRATE PREPARATION

The wax must be applied on robust and durable substrates, which are clean, dry and free from dust, grease and other substances reducing adhesion. Limestone stuccos can be waxed after they are completely dry, i.e. 7 days after application.



Art of inspiration

PRODUCT PREPARATION

The product is ready for use.

APPLICATION METHOD

Using INOX Venetian float, apply a very thin layer of the Francesco GUARDI wax onto a dry and clean surface of approx. 1 m² of stucco. After approx. 3 minutes, polish with a soft fabric, such as a flannel cloth, or using a car polisher until a good shine is obtained. Repeat the procedure over the entire surface.

ADDITIONAL INFORMATION

The wax should be applied at a substrate and ambient temperature of +10°C to +25°C, avoiding direct sunlight during both the application and polishing of the wax. LAKMA® SAT shall not be responsible for the quality of decorative works in the event where the indicated instructions are not followed.

TECHNICAL DATA

Tools	Soft cloth, INOX Venetian float
Number of layers	1 or 2
Coverage for a single layer	10 to 15 m ² /package
Next coat	After 30 hours
Drying time	30 minutes
Cleaning of the tools	Water
Colour scheme	Colourless

The technical data are provided for the temperature of +20°C and the relative air humidity of 60%.

PACKAGING DETAILS

Unit package capacity	Number of packages in external packaging	Number of packages on a pallet	Weight of a full pallet
400 ml	12	480	approx. 312 kg



Art of inspiration

STORAGE

48 months from the date of production, in sealed containers, at temperatures from +5°C to +35°C

HEALTH AND SAFETY / FIRE PREVENTION INSTRUCTIONS

HEALTH AND SAFETY / FIRE PREVENTION



Caution

H226 Flammable liquid and vapour.

EUH066 Repeated exposure may cause skin dryness or cracking.

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat / sparks / open flames / hot surfaces. – No smoking.

P233 Keep container tightly closed.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P501 Dispose of contents/container to an authorised waste collection point, in accordance with local regulations.

Updated on 22 Jul 2018

The information in this Technical Data Sheet is intended to ensure optimum use of the product. However, it does not constitute the basis for legal liability of the Manufacturer, since the workmanship conditions remain beyond its control. The procedures suggested are deemed to be universal. However, each user of this material must do all they can, including verification of the end product, to make sure that the materials delivered are suitable for the particular intended purposes. We accept no liability for the combination of our products with any third-party products. The above-mentioned data, instructions and recommendations are based on our best knowledge, research and experience, and have been provided in good faith, according to the principles applicable in our company and at our suppliers. The Manufacturer reserves the right to make changes in the subsequent editions without prior notification to the consumers. With publication of this Technical Data Sheet, all previous data sheets regarding this product are no longer valid.