



Art of inspiration

RUST EFFECT PAINT

Francesco GUARDI Collezione

PRODUCT DESCRIPTION

The rust effect paint by Francesco GUARDI

Collezione is a ready-to-use modern paint, produced on the basis of high-quality acrylic resin, special fillers and metallic pigments. It is designed for decorating exterior and interior walls and ceilings of such areas as living rooms, corridors, kitchens, bathrooms, as well as for finishings in restaurants, hotels and other areas, where a raw effect of rusty surfaces is desired.

- resistant to abrasion
- easy to apply
- produces multiple effects
- highly efficient
- for indoor and outdoor application

INTENDED USE

The rust effect paint is designed for decorating interior walls and ceiling made of cement plaster, cement/lime render, concrete, drywall, gypsum finishing coats, etc. in such areas as living rooms, halls, corridors, kitchens, and bathrooms, as well as for finishings in restaurants, hotels, conference rooms and other areas where a unique decorative effect is desired. It also works well for painting exterior walls in single- and multi-family buildings, and public access areas.

APPLICATION METHOD

Surface preparation: The rust effect paint must be applied on robust and durable substrates, which are clean, dry and free from dust, grease and other substances reducing adhesion. Prior to application of the paint, a well-dried and seasoned substrate should be primed using the Francesco GUARDI Latex primer paint in the "black pearl" colour or the GUARDI Deco primer in the KAM/021 colour. If the paint is used outdoors, the priming procedure should be carried out using only the GUARDI KAM/021 primer. Fresh cement and cement/lime renders should be primed after approx. 4 weeks, while gypsum renders – approx. 2 weeks after application. Gypsum finishing coats and surfaces made of drywall must be dedusted and then primed, e.g. using Akryl G or Fixgrunt U. It is important to make sure that the surface





Art of inspiration

does not leave any white dust when rubbed by hand. If necessary, use the primer twice, and then – after an appropriate time – apply the Francesco GUARDI Latex primer paint in the “black pearl” colour or the GUARDI Deco primer in the KAM/021 colour. Walls covered with wallpaper: thoroughly remove the wallpaper and wash away the layers of glue using water and painter's soap, and allow to dry completely. Areas contaminated with mould or fungi should be cleaned mechanically and disinfected using the Biotox Total algicide and fungicide.

The rust effect decorative paint can be applied after the priming layer has dried, i.e. approx. 6 hours after completion of painting if optimum drying conditions were provided (temperature +20°C, humidity of 60%).

Application method: Before using the paint, it is necessary to arrange for component A and component B, as well as plan the sequence and manner of application. Mix the product before use. Apply component A on a previously primed surface using a thread roller or a sponge with big pores, in stamping or spreading movements. It is recommended to apply component B “wet-on-wet”, i.e. preferably when component A is still damp, which will produce the effect of overlapping colours that imitate rust. It is also possible to apply component B after the surface with component A has already dried. Then, component B should be applied with a sponge with big pores using stamping or spreading movements. The intensity of coating depends on the expected final result.

Additional information: The decorative rust effect paint should be applied at substrate and ambient temperatures of +10°C to +25°C, avoiding direct sunlight during both the application and drying of the paint.

TECHNICAL DATA

Tools	Sponge, thread roller
Number of layers	1 to 2 – depending on the effect you want to achieve
Coverage for a single layer	10 to 12 m ² per 0.5 litre container – depending on the substrate texture, the expected results, and the painter's experience
Density	Approx. 1.1 kg
Drying time	At least 2 hours
Cleaning of the tools	Water
Colour scheme	Shades of ginger-brown



Art of inspiration

PACKAGING DETAILS

Unit package capacity	Number of packages in external packaging	Number of packages on a pallet	Weight of a full pallet
Component A – 0.5 litre	6	240	approx. 337 kg
Component B – 0.5 litre	6	240	approx. 337 kg

STORAGE

36 months from the date of production, in sealed containers, at temperatures from +5°C to +35°C

APPROVALS, ATTESTATIONS, STANDARDS

VOC limits according to Dz.U. 07.11.72 Cat. A/I/WB	Permissible VOC content: 200 g/l (2010) Maximum content in the product: 25.0 g/l
Certificate of Conformity	No. BL1/17/2017 dated 25.05.2017
Standards	PN-EN – 13300: 2002 "Water-borne coating materials and coating systems for interior walls and ceilings."

HEALTH AND SAFETY / FIRE PREVENTION INSTRUCTIONS

Apply basic health and safety rules during works.

Non-flammable. Store in closed containers, at temperatures from 5°C to +35°C.

Keep out of reach of children.

Updated on 08 May 2018

The information in this Technical Data Sheet is intended to ensure optimum use of the product. However, it does not constitute the basis for legal liability of the Manufacturer, since the workmanship conditions remain beyond its control. The procedures suggested are deemed to be universal. However, each user of this material must do all they can, including verification of the end product, to make sure that the materials delivered are suitable for the particular intended purposes. We accept no liability for the combination of our products with any third-party products. The above-mentioned data, instructions and recommendations are based on our best knowledge, research and experience, and have been provided in good faith, according to the principles applicable in our company and at our suppliers. The Manufacturer reserves the right to make changes in the subsequent editions without prior notification to the consumers. With publication of this Technical Data Sheet, all previous data sheets regarding this product are no longer valid.